


Picture may differ from original product

AQPU Series

Wheel Diameter × Wheel Width 155 x 32mm

YJ-12038406135014 Copy model no.

Wheel Diameter（D）	Tread Pattern	Load Capacity at 6 km/h
155mm	—	**170kgs**

- Good elasticity，Reduced pushing resistance，Improved equipment maneuverability，Good abrasion resistance
- Excellent hydrolysis resistance
- Suitable for tropical regions and humid working environments
- QPU，Black，Transverse-grooved surface
- Increases floor traction，Effectively improves slip resistance
- Inner bushing：Aluminum core

Product descriptions are for reference only. The actual product shall prevail.

Product Data Sheet (Metric) | 3D Drawing Request

3D drawings are for members only. Please log in to download.

Product Data Sheet

Metric | Imperial

Wheel Diameter（D）	**155mm**	Wheel Width（T2）	**32mm**
Wheel installation — Hub Lenth (T1)	**27.5mm**	Wheel Mounting Bore Diameter	**13.8 mm**
Keyway Width	**5mm**	Wheel Keyway Depth (H)	**16.4mm**
Load Capacity (Static)	**300kgs**	Load Capacity at 4 km/h	**200kgs**
Load Capacity at 6 km/h	**170kgs**	Load Capacity at 10 km/h	**140kgs**
Load Capacity at 16 km/h	**80kgs**	Hardness Of Tread	**60±5° Shore A**
Temperature	**-20°C to +70°C**	Tread Pattern	—
Wheel centre/ rim		Non-Marking	**Y**
Conductive	**N/A 10^6/～10^9/Ω**	Anti	**N/A**
Weight	**0.67kgs**	Standard	**ISO22883**

* For any deviation between metric and imperial spec, please refer to the metric spec.

Performance

Rolling Smoothness
Max. 5 points Score: 5

Quiet Operation
Max. 5 points Score: 5

Floor Surface Preservation
Max. 5 points Score: 5

Downloads

PDF **YJ-120384061350143.pdf**
Product Data Sheet (Metric)

3D **12038406135014.rar**
3D drawings are for members only. Please log in to download.

© 2026 DERSHENG CO., LTD. All rights reserved.